



Haze Away

Product Data Sheet

3-in-1 GROUT HAZE REMOVER

BENEFITS:

- Highly effective multi-purpose formulation that removes cement, epoxy and urethane grout haze
- Removes latex additive film from tile
- Removes light grout residue within ten days of grouting
- Non-flammable
- Use interior and exterior

DESCRIPTION: VanHearron's Haze Away is safe and effective in removing grout haze left by cement, epoxy, and urethane grout.

USES: Haze Away can be used for the removal of all cement based, epoxy and urethane grouts' haze from natural stone, polished unglazed porcelain, ceramic tile, grout, concrete and masonry surfaces.

ADVANTAGES: Haze Away removes grout haze from travertine, limestone, polished unglazed porcelain, slate, sandstone, grout, and masonry surfaces. Add Haze Away to clean-up water to reduce the water needed and the time it takes for grout clean up. Use Haze Away full-strength to remove light grout residue within 10 days of grouting.

LIMITATIONS: Not for use on marble or terracotta. Prevent product from contacting surrounding surfaces such as carpet, glass, landscaping, metal, paint and wood.

APPLICATION: **Read entire label before using. Use only as directed.** Add approximately 3 ounces of Haze Away to every gallon of water used in the grout clean-up process. Apply Haze Away liberally on grout residue using a sponge, mop, paint-pad applicator, paint roller or brush. Allow Haze Away to dwell on the surface for up to 10 minutes. Agitate with a scrub pad or other comparable non-marring scrubbing tool until cement grout residue is removed from the surface. Some grout residue may require additional applications.

NOTE: *High-pressure (1000 – 3000 PSI) sprayers are highly effective at rinsing away grout residue when used in conjunction with Haze Away. Wipe surface completely dry using a clean, dry, white cotton or microfiber towel.*

WARNING: *Keep out of reach of children. May be harmful if swallowed. May irritate eyes and skin.* It is good practice to always wear protective clothing, gloves, and eye protection when handling Haze Away. In the event of eye contact, continuously rinse eyes for a minimum of 15 minutes. If irritation persists, seek medical attention. If product gets on skin, wash with soap and water. If irritation persists, seek medical attention. If swallowed, DO NOT induce vomiting. Seek medical attention.

COVERAGE: Approximately 600 to 1200 square feet per quart depending on type of surface, porosity, texture, temperature and method of application.

COMPLIANCE AND HANDLING: Complies with all federal, state, and local VOC regulatory requirements. Use and store between 40 F and 100 F (4 C and 38 C). Store in original container only. Close securely after each use. Shelf life expectancy is at least 1 year.

AVAILABILITY: VanHearron's Haze Away is available in 1 gallon and 32 ounce bottles.

APPEARANCE: Slightly yellow/orange

PHYSICAL STATE: Liquid

ODOR: Slightly acrid

pH: (Typical) 2.0

BOILING RANGE: Not determined

VISCOSITY: Not determined.

EVAPORATION RATE (Butyl Acetate = 1): Slower than butyl acetate

SPECIFIC GRAVITY (H₂O = 1): 1.14

SOLUBILITY IN WATER, by wt.: 100 %

VanHearron's state-of-the-art protective treatments have developed a reputation among architects and design professionals as the premier solution for construction chemicals. VanHearron, Inc. is dedicated to solving the destructive influence water intrusion and other elements have on tile and natural surfaces.

Technical service engineers and chemists are available to answer questions on product performance, application methods and chemical composition.

Disclaimer/Warranties: 100% satisfaction guaranteed when used as directed. Contact VanHearron for exclusive remedy or either refund of purchase price or replacement of product. Proof of purchase within one year of purchase required. Neither manufacturer nor seller have any knowledge or control concerning the purchaser's use of the product. No expressed warranty is made by manufacturer or seller with respect to the results of any use of the product or container wherein the product is packaged. No implied warranties including but not limited to an implied warranty of merchantability or an implied warranty of fitness for a particular purpose are made with respect to the product. User shall rely on his or her own information and tests to determine suitability of the product for the intended use. User assumes all risk and liability resulting from use of the product. Neither manufacturer nor seller assume any liability for personal injury, loss, or damage resulting from the use of the product. We do not suggest or guarantee that any hazards listed herein are the only ones which may exist. In the event that the product shall prove defective, buyer's exclusive remedy shall be that the seller or manufacturer shall, upon written request of buyer, replace any quantity of the product which is proven to be defective or shall, at its option, refund the purchase price of the product upon return of the product. Manufacturer shall not be responsible for use of this product in a manner to infringe on any patent held by others.