



NATURAL LOOK SEALER

Product Data Sheet

STAIN RESISTANT FOR EXTERIOR STONE, DECORATIVE CONCRETE, AND PAVERS

BENEFITS

- Repels stains, oil, food products, graffiti
- Excellent resistance to water intrusion
- No change in surface appearance
- Breathable system
- ZERO V.O.C.

Description:

Natural Look Exterior Sealer is a clear, penetrating, breathable, ZERO VOC, water, oil and graffiti resistant treatment for exterior stone, decorative concrete, and pavers. Natural Look Exterior Sealer penetrates the surface and bonds physically and chemically to the substrate, resulting in solid 10 year protection by reducing the ingress of water-borne and oil-based contaminants into the surface. It is also suitable for use as an anti-graffiti treatment. Natural Look Exterior Sealer keeps treated outdoor surfaces cleaner and easier to maintain.

Usage:

Natural Look Exterior Sealer is suitable for a wide variety of applications, including pavers, decorative concrete, exterior stone, swimming pool surrounds, patios, outdoor kitchens and entertaining areas. It is unaffected by salt and is excellent around saltwater pools and driveways/sidewalks exposed to winter salt application.

Advantages:

Natural Look Exterior Sealer is designed to work without changing the natural appearance of the surface and is able to repel stains, oil and food products as well as graffiti.

Limitations:

Not intended for below-grade waterproofing. Should not be applied if the surface temperature is below 20° F or above 100° F, if rain is expected within six hours following application, or if high winds or other conditions prevent proper application. If rain has preceded the application, the surface should be allowed to dry at least 24 hours. Caution should be taken with windows, motor vehicles, vegetation and adjacent surfaces. Check compatibility before application.

Application:

All surfaces must be cleaned to remove all traces of dirt, dust, efflorescence, mold, salt, grease, oil, asphalt, laitance, curing compounds, paint, coatings and other contaminants. Acceptable surface cleaning methods include shot blasting, sandblasting, water blasting and chemical cleaners. Check with your VanHearron representative to verify suitable cleaning methods, products and that the surface preparation is adequate. Before applying, it is recommended that preliminary tests be carried out to determine usage and to test the effectiveness of the treatment. Depending on the porosity of each designated surface, coverage rates can vary. Typical coverage is approximately 200-2000 square feet per gallon depending on specific application and surface porosity. Natural Look Exterior Sealer should be applied by low-pressure (15 to 25 psi) pumping

equipment with a wet fan type spray nozzle. Alternate methods include nap roller (1") or by brush.

Horizontal surfaces should be treated until material puddles or stands on the surface. After ten minutes sweep, squeegee, or mop any remaining material to dry areas.

Vertical surfaces should be treated using a wet-on-wet technique by applying from the bottom up with six to eight inch run down from the bottom of the spray pattern.

During application, precautions should be taken to protect the surrounding area from overspray and run off. Natural Look Exterior Sealer will not etch glass but will leave a residue on non-porous surfaces.

Precautions:

Natural Look Exterior Sealer should be kept closed when not in use and should be stored at temperatures between 35° F and 120° F. Care should be taken to prevent moisture condensation in the container. Please refer to the Material Safety Data Sheet for more detailed information.

Availability:

Natural Look Exterior Sealer is available in 1 and 5 gallon containers distributors throughout the United States.

Technical Services: Technical service engineers and chemists are available to answer questions on product performance, application methods and chemical composition.

Appearance

Physical state: liquid

Form : liquid

Color : clear, opaque, yellowish

Odor: No applicable data available.

Odor threshold : No applicable data available.

pH: 4 - 6

Melting point/range: No applicable data available.

Boiling point: 100 °C (212 °F) at 760 mm Hg

Flash point: does not flash

Evaporation rate: No applicable data available.

Flammability (solid, gas): No applicable data available.

Upper explosion limit: No applicable data available.

Lower explosion limit: No applicable data available.

Vapour Pressure: No applicable data available.

Vapour density: No applicable data available.

Specific gravity: 1.1

VanHearron's state-of-the-art protective treatments have developed a reputation among architects and design professionals as the premier solution for construction chemicals. VanHearron, Inc. is dedicated to solving the destructive influence water intrusion and other elements have on tile and natural surfaces.

Technical service engineers and chemists are available to answer questions on product performance, application methods and chemical composition.

Disclaimer/Warranties: 100% satisfaction guaranteed when used as directed. Contact VanHearron for exclusive remedy or either refund of purchase price or replacement of product. Proof of purchase within one year of purchase required. Neither manufacturer nor seller have any knowledge or control concerning the purchaser's use of the product. No expressed warranty is made by manufacturer or seller with respect to the results of any use of the product or container wherein the product is packaged. No implied warranties including but not limited to an implied warranty of merchantability or an implied warranty of fitness for a particular purpose are made with respect to the product. User shall rely on his or her own information and tests to determine suitability of the product for the intended use. User assumes all risk and liability resulting from use of the product. Neither manufacturer nor seller assume any liability for personal injury, loss, or damage resulting from the use of the product. We do not suggest or guarantee that any hazards listed herein are the only ones which may exist. In the event that the product shall prove defective, buyer's exclusive remedy shall be that the seller or manufacturer shall, upon written request of buyer, replace any quantity of the product which is proven to be defective or shall, at its option, refund the purchase price of the product upon return of the product. Manufacturer shall not be responsible for use of this product in a manner to infringe on any patent held by others.